

# **Ambience** Hardwood Shutter

### **Product Information**

The **Ambience Hardwood Shutter** features a light weight frame with a concealed aluminium control rod which allows for full closure of blades in two positions. This provides clear and uninterupted visibility through the blades.

Available with elliptical blades in 64mmm, 89mm and 114mm, painted shutters are made from finger jointed Poplar, coated using a polyurethane coating system. Stained shutters are made from basswood, which are stained and then coated using a nitro-cellulose lacquer system.

A range of functional, quality hardware is supplied with the Ambience Hardwood shutter, providing you with the complete package.

#### Further Information

To find out more information phone Verosol Customer Care on 1800 721 404 or visit www.verosol.com.au



#### **Technical Information**

Product Code	S206.0				
Product Name	Ambience Hardwood Shutter				
Dimensions - Width Range	Single & Hinged Shutter	400mm Minimum - 1050m	400mm Minimum - 1050mm Maximum (max. 920mm for 64mm blade)		
	Double Hinged	400mm Minimum - 600mr	400mm Minimum - 600mm Maximum		
	Sliding Shutter	700mm Minimum - 1050m	700mm Minimum - 1050mm Maximum		
	Bi-Fold Shutter	400mm Minimum - 600mr	400mm Minimum - 600mm Maximum		
Dimensions	Height Range	400mm Minimum - 3000m	400mm Minimum - 3000mm Maximum		
Max Area	Single, Hinged and Sliding	ngle, Hinged and Sliding 3.15m <sup>2</sup>			
	Double Hinged & Bi-Fold	Bi-Fold 1.8m <sup>2</sup>			
Minimum Reveal Depth	Blade Size	64mm	89mm	114mm	
	No Frame	54mm	67mm	79mm	
	Z Frame	39mm	52mm	64mm	
	L Frame	54mm	67mm	79mm	
	Fixed	54mm	67mm	79mm	
	Bi-Fold	100mm	100mm	100mm	
Material	Painted: Poplar Hardwood				
	Stained: Basswood				
Operation	Single, Hinged, Double Hinged, Sliding and Bi-fold Systems				
Mid Rail Position	Mandatory for all shutters over 1800mm in drop				
	Specify height of mid rail to centre and note if critical mid rail heigh is required				
Split Controls	Blades spanning over 1200mm in drop will have a control rod split in half - specify if you require the split at a specific height				
Control and Handle	Туре	Aluminium Control Rod			
	Operation	Operation by rod or blades			

# **Ambience** Hardwood Shutter

## **Technical Information**

Finishes	Paint	Poplar hardwood coated with a polyurethane coating system Colour range as shown below
	Timber Grain	Stained and coated with a nitro-cellulose lacquer system Colour range as shown below
	Special Order	Special paints can be made to order, refer to Dulux World of Colour deck
Installation	The installation of shutters externally may require the services of a qualified technician	

## Poplar Painted Colour Range



## Basswood Stained Colour Range

