

Ambience Roller Blinds

All Roller Blinds Product and Bracket Installation Guide

R200.0 / R201.0 Ambience Roller Blind - Chain / Twin				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
300mm	3000mm	300mm	3000mm	6m ² without spring assist
		850mm*	3000mm	8m ² with spring assist
Motorised Operation				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
600mm	3000mm	300mm	3000mm	9m ²

*Spring Assist minimum

R202.0 / R204.0 / R203.0 Ambience Roller Blind - Multi-Link / Uni Joint / Twin Multi-Link				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
300mm	3000mm	300mm	3000mm	15m ² over 3 sections
		850mm	3000mm	
Motorised Operation				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
600mm	3000mm	300mm	3000mm	24m ² over 4 sections

*Spring Assist minimum

R205.0 / R206.0 Ambience Blackout Roller Blind - Chain / Multi-Link				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
500mm	3000mm	500mm	3000mm	6m ² without spring assist
		850mm*	3000mm	8m ² with spring assist
Motorised Operation				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
600mm	3000mm	500mm	3000mm	9m ²

*Spring Assist minimum

R200.3 Ambience Heavy Duty - Chain / Multi-Link / Uni-Joint				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
600mm	3000mm	600mm	3000mm	24m ² over 3 sections
		1200mm*	3000mm	
Motorised Operation				
Width [w]		Drop [d]		Maximum Area
Minimum	Maximum	Minimum	Maximum	
600mm	3000mm	600mm	3000mm	40m ² over 4 sections

Type of Installation:

