Expand your comfort zone

Ambience Polyresin Shutter

Product Information

The **Ambience Polyresin Shutter** features Aluminium insert on the blades with frames to offer strength and protection against warping.

Available with elliptical blades in 64mm and 89mm, painted shutters are made from PVC, coated using a polyurethane coating system.

A range of functional, quality hardware is supplied with the Ambience

Polyresin Shutter, providing a complete package.

Further Information

To find out more information phone Verosol Customer Care on 1800 721 404 or visit www.verosol.com.au



Verosol

Technical Information

Product Code	S214.0				
Product Name	Ambience Polyresin Shutter				
Dimensions - Width Range	Single & Hinged Shutter	400mm Minimum - 1050mm Maximum (max. 920mm for 64mm blade)			
	Double Hinged	400mm Minimum - 600mm Maximum	400mm Minimum - 600mm Maximum		
	Sliding Shutter	700mm Minimum - 1050mm Maximum	700mm Minimum - 1050mm Maximum		
	Bi-Fold Shutter	400mm Minimum - 600mm Maximum	400mm Minimum - 600mm Maximum		
Dimensions	Height Range	400mm Minimum - 3000mm Maximum	400mm Minimum - 3000mm Maximum		
Max Area	Single, Hinged and Sliding	3.15m ²	3.15m ²		
	Double Hinged & Bi-Fold	1.8m ²	1.8m ²		
Minimum Reveal Depth	Blade Size	64mm	89mm		
	No Frame	54mm	67mm		
	Z Frame	39mm	52mm		
	L Frame	54mm	67mm		
	Fixed	54mm	67mm		
	Bi-Fold	100mm	100mm		
Material	High strength polymer resin with aluminium blade inserts				
Operation	Single, Hinged, Double Hinged, Sliding and Bi-fold Systems				
Mid Rail Position	Mandatory for all shutters over 1800mm in drop				
	Specify height of mid rail to centre and note if critical mid rail heigh is required				
Split Controls	Blades spanning over 1200mm in drop will have a control rod split in half - specify if you require the split at a specific height				
Control and Handle	Туре	Aluminium Control Rod			
	Operation	Operation by rod or blades			

Turn over for more details

Ambience Hardwood Shutter

Technical Information

Finishes	Paint	Polymer resin coated with a polyurethane coating system Colour range as shown below
Installation	The installation of shutters externally may require the services of a qualified technician	

Colour Range

