

Framed Pleated Blind

Product Information

Verosol's **Framed Pleated Blind** combines the versatility of a standard pleat and easy installation. The ideal solution for heat and light control, and the blind almost disappears when raised. Simple and elegant with a small stack height and short projection, giving you an uninterrupted view from your home or office window.

Perfect for use on tilt + turn windows or applications that require no drilling, as well as an ideal solution for boats and motor homes.

Further Information

To find out more information phone Verosol Customer Care on 1800 721 404 or visit www.verosol.com.au



Technical Information

Product Code	P217.0	
Product Name	Framed Pleated Blind	
Operation	Hand Operation	
Dimensions	Width	300mm min - 1000mm max
	Drop	200mm min - 2000mm max
	Maximum Area	2m ²
Head Rail	Material	Extruded Aluminium Alloy
	Dimensions	40mm W x 15mm H
Bottom Rail	Material	Extruded Aluminium Alloy
	Dimensions	30mm W x 18mm H
	Paint	Electrostatic Powder Coated and Baked
Inner Rail	Material	UV Stabilised Acrylonitrile Butadiene Styrene [ABS] Plastic
Lift and Blind Cords	Material	Braided Polyester [minimum diameter: 2.2mm]
	Colour	Coordinated - Refer to "Pleated Rail Chart"
Cord Position	Lift Cords 70mm from edge; Maximum spacing 500mm	
Installation	Material	Magnetic Tape
	Operation	Top or Face Fixing - concealed when installed