Expand your comfort zone

# **471 Sanctuary**

Blockout Curtain Fabric [3200mm Wide - Continuous]





Flame Retardant



Curtains

# Decorative woven blockout curtain fabric

### **Features**

- Part of the Verosol Everyday Living Collection Drapery fabrics developed to the highest quality standards
- Sanctuary is a continuous blockout curtain fabric available in a selection of 10 contemporary colours
- Woven from 100% Polyester ensures soft drapability and easy care
- Sanctuary curtain fabrics are flame retardant making them ideal for both residential and commercial applications
- Coordinated with Everyday Living sheers allows design freedom throughout the entire range

### **Care Instructions**

#### Care Code 6

Regular care will minimise the need for additional cleaning. Gently vacuum with appropriate attachment. Always exercise caution when spot cleaning. Test cleaning on non-exposed surface. Avoid excessive rubbing and abrasion. Remove hooks rings and trims before cleaning. Cleaning possible shrinkage 3%.

please turn over for complete care instructions

For more information visit verosol.com.au or call 1800 721 404





Everyday Living

# **471 Sanctuary**

**Blockout Curtain Fabric** 

| Fabric Density                      | Blockout                     | Silicon finish on acrylic foam coated backing                         |                  |                                                        |                                                  |
|-------------------------------------|------------------------------|-----------------------------------------------------------------------|------------------|--------------------------------------------------------|--------------------------------------------------|
| Composition                         | 100% Polyester               | PVC Free                                                              | Halogen Free     | Phthalate Free                                         | Formaldehyde Free                                |
| Weight                              | 230gsm                       |                                                                       |                  |                                                        | ••••••                                           |
| Width                               | 3200mm                       | Continuous                                                            |                  |                                                        |                                                  |
| Drapery                             | Compliant to AS2663.1-1997 - | Category 3 - I                                                        | High Performance | Care Code                                              | 6                                                |
| Colour Fastness                     | Light                        | [ISO 105-B02]                                                         | ]>6              |                                                        | • • • • • • • • • • • • • • • • • • • •          |
|                                     | Dry Cleaning                 | [ISO 105-D01:1993]<br>Colour change: 5<br>Staining solvent: 5         |                  | Dimensional Change due to<br>Hanging [AS2663.1.B-1997] | Dimensional Change %<br>Warp: +0.2<br>Weft: +0.1 |
|                                     | Rubbing                      | [ISO 105-X12:<br>Dry: 4<br>Wet: 5                                     | 1993]            |                                                        |                                                  |
|                                     | Washing                      | [ISO 105-C06:1994, B1S]<br>Colour change: 5<br>Staining multifibre: 5 |                  | Dimensional Change due to<br>Laundering [ISO 6330.7BA] | Dimensional Change %<br>Warp: -2.0<br>Weft: 0.0  |
| Flame Retardancy<br>[AS1530.2-1993] | Flammability Index           | 4 Range [C                                                            | 9-100]           |                                                        |                                                  |
| Certification                       | ISO9001:2000                 | •••••                                                                 |                  |                                                        | •••••••••••••••••••••••••••••••••••••••          |
| Suitable Products                   | Curtains                     | •••••                                                                 |                  |                                                        |                                                  |

## **Care Instructions**

#### Care Code 6

Regular care will minimise the need for additional cleaning. Gently vacuum with appropriate attachment. Always exercise caution when spot cleaning. Test cleaning o non-exposed surface. Avoid excessive rubbing and abrasion. Remove hooks rings and trims before cleaning. CLEANING POSSIBLE SHRINKAGE 3%. Drycleaning: Use specialist curtain drycleaners as recognised by the Soft Furnishings Industry Association of Australia Inc. For perchlorethylene. Solvent temperature 18 - 200 C, no moisture, gently cycle, moderate (approx 50% capacity) loading minimise mechanical action. One bath Drycleaning Procedure: 3 minutes passing through the filter, reduced mechanical action, 2 minutes drain to tank or still, 2 minutes extract to tank or still. Two Stage Drying Procedure: 25 minutes drying at 550 C, then 6 minutes drying at 350 C. Deodorise 6 minutes or until curtains are cool. For white Spirit or Hydrocarbon. Standard Drycleaning practices are appropriate. Hang curtains upon removal from machine. Do not iron/press coated side. Warm iron/press on fabric side only. Washing: Curtains are heavy when wet. Professional we cleaning recommended. DO NOT WASH IN DOMESTIC WASHING MACHINE. Hand wash in cool to warm water (max 40o C) Mild detergents such as wool mixes are recommended. Do not bleach, soak, rub or wring. Drip dry in shade. Do not tumble dry. Hang curtains by their hooks to avoid coated sides touching. Do not use pegs. Do not fold curtains over clothes lines. Do not iron/press coated sides. Worm iron/press on fabric side only. Please note that the silicon finish can be cleaned with a damp cloth on the coated side. \*For detailed code of practice for cleaning coated fabrics. Drycleaners are encouraged to contact the DIA.



#### **Colour Range**

Copyright 2020 Verosol Australia [ABN 36 006 221 003]

Copyright 2020 Version Australia (ABN 36 006 221 003) Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. Specifications and other data are based on information available at the time of preparation of thi document and are subject to production tolerances and/or change without prior notice. Drapery fabrics are tested for compliance to AS2663.1-1997. Flame retardancy information is tested to [AS 1530.2-1993]. Please note that test results may vary slightly depending on fabric colour. Note: All colours are a representative only, please request a sample for accurate colour representation at www.verosol.com.au.