



# 744 Haven



## An exclusive linen look blockout solution with matching non transparent fabric

#### **Features**

- A premium jacquard fabric with exceptional feel and linen appearance
- Designed for maximum privacy and room darkening
- Modern designer colour palette also available in matching light filtering fabric
- Suitable for Roller Blinds and Panel Glides

#### **Care Instructions**

For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information visit verosol.com.au or call 1800 721 404





green building council australia MEMBER 2019-2020

## 744 Haven Blockout

Fabric Density	Blockout		Pattern	Linen-Look Weave
Composition	100% Polyester with Acry	100% Polyester with Acrylic Polymer Foam Coating		Warp 69.71N
Weight	400gsm ± 5%			Weft 60.44N
Thickness	0.59mm ± 5%		Dimensional Stability	Warp 1078.58N
Width	3000mm			Weft 1110.45N
Colour Fastness	5 [ISO 105-B02]	5 [ISO 105-B02]		AS2663-1999
Certification	Oeko-tex 100 Class IV	ISO 9001:2008	ISO 14001:2004	ISO 50001:2011
	ISO 18001:2007	REACH Compliant	• • • • • • • • • • • • • • • • • • • •	
Suitable Products	Roller Blinds	Panel Glides		
••••••	•••••••••••••••••••••••••••••••••••••••	•••••••••••••••••••••••••••••••••••••••	• • • • • • • • • • • • • • • • • • • •	•••••••••••••••••••••••••••••••••••••••

Colour Range							
1000 White	2000 Cream	3000 Taupe	4000 Linen	6000 Grey	7000 Dark Grey	8000 Slate	9000 Black

© Copyright 2018 Verosol Australia [ABN 36 006 221 003] Updated March 2020 Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. All presented data calculated in WIS 3.0.1 (Advanced Windows Information System) with spectral data. Specifications and other data are based on information available at the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Flame retardancy information is sourced from AWTA testing results [ASIX25 1530.3-1999]. Please note that test results may vary slightly depending on fabric colour. [4mm Single Glass reference glazing A EN 14501], [High Performance Glazing reference glazing D EN 14501] according to EN 14500. Note: All colours are a representative only, please request an A4 sample for accurate colour representation at www.verosol.com.au.