
Verosol

432 Verocell Harbour





45mm Cellular Blinds



Privacy with a natural look and feel

Features

- With an irregular linear pattern, Harbour is available in a range of six soft natural colours and a white backing that provides a uniform appearance from the outside regardles of colour
- The cellular design of the blockout fabric featuring a silver foil coating on the inside of the cells that creates an ideal indoor environment regulating temperature and improving acoustic quality, while saving energy costs at the same time
- Harbour is also available in a semi-transparent fabric
- Suitable for 45mm Cellular Blinds
- ٠

Care Instructions

For regular maintenance of your cellular blinds, use a soft feather duster or vacuum-clean with a soft brush dusting attachment in a low setting. Always exercise caution when spot cleaning. Use a clean lint-free cloth or sponge and dip it in warm water. Dry gently with a clean towel. Caution: Do not clean windows with any chemical products which make direct or indirect contact with the blind

For more information visit verosol.com.au or call 1800 721 404



432 Verocell Harbour Blockout



Blockout Fabric Density Composition 100% PES Weight 169gsm ± 10% 0.21mm ± 10% Thickness Cell Size 45mm Fabric Width 3660mm 4-5 [ISO 105-B02] Colour Fastness Flame Retardancy Non Fire Retardant Certification Oeko-Tex 100 Class IV 45mm Cellular Blinds Suitable Products

Fabric Colours	5400	5269
Solar transmittance	0%	0%
Solar reflectance	71%	71%
Solar absorptance	29%	29%
Visible Light Transmission	0%	0%
Light Absorption		
Light Reflection		
UV transmittance		
Openness factor (nominal)		
Gtot value		0.34
FC-value	0.57	0.57
FC-class 1.2 [HIGH] Classification	2	2

Colour Range | 45mm Cellular Fabric



© Copyright 2023 Verosol Australia (ABN 36 006 221 003) Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. Thermal and optical values are tested in accordance to the European standard DIN EN 14501 and calculated and measured using DIN EN 410 for determination of luminous and solar glazing characteristics, FC-Value tested in accordance to EN5022 Reference Glazing-C. FC Classification Value Ranges: 1-FC>0.19, 2-FC>0.39, 3-FC>0.59, 4-FC>0.79, 5-FC>0.89, Secilications and other data are based on information available at the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Please note that test results may vary slightly depending on fabric colour. Note: All colours are representative only.