Verosol

441 Verocell Province

Semi Transparent



45mm Cellular Blinds



Flame-retardant and excellent thermal qualities

Features

- Province FR is characterized by its flame retardant and thermal qualities. Thanks to its intelligent cellular structure, the nonwoven 45mm fabric helps to save energy throughout the year. Province FR is also available in a blockout fabric
- Semi-transparent fabric perfect for softening the light from outside, whilst providing privacy inside
- Featuring a clean natural palette of 4 colours, bringing simplicity and character to transform any interior
- White base colour on the backing regardless of the colour providing a uniform look from the outside
- Suitable for 45mm Cellular Blinds

Care Instructions

For regular maintenance of your cellular blinds, use a soft feather duster or vacuum-clean with a soft brush dusting attachment in a low setting. Always exercise caution when spot cleaning. Use a clean lint-free cloth or sponge and dip it in warm water. Dry gently with a clean towel. Caution: Do not clean windows with any chemical products which make direct or indirect contact with the blind

For more information visit verosol.com.au or call 1800 721 404



441 Verocell Province



Semi Transparent

Fabric Density	Semi Transparent
Composition	100% PES
Weight	169gsm ±10%
Thickness	0.27mm ± 10%
Cell Size	45mm
Fabric Width	3660mm
Colour Fastness	4-5 [ISO 105-B02]
Flame Retardancy	NFPA 701
Certification	Oeko-Tex 100 Class IV
Suitable Products	45mm Cellular Blinds
••••••	•••••••••••••••••••••••••••••••••••••••

Fabric Colours	7734
Solar transmittance	7%
Solar reflectance	69%
Solar absorptance	24%
Visible Light Transmission	5%
Light Absorption	
Light Reflection	
	3%
Openness factor (nominal)	0%
Gtot value	
FC-value	0.58
FC-class 1.2 [HIGH] Classification	2

Colour Range | 45mm Cellular Fabric



© Copyright 2023 Verosol Australia (ABN 36 006 221 003) Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. Thermal and optical values are tested in accordance to the European standard DIN EN 14501 and calculated and measured using DIN EN 410 for determination of luminous and solar glazing characteristics, FC-Value tested in accordance to ENS022 Reference Glazing-C. FC Classification Value Ranges: 1-FC>0.19, 2-FC>0.39, 3-FC>0.59, 4-FC>0.79, FC>0.89, Secifications and other data are based on information and allow and the relatare based on information and the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Flame retardancy information is sourced from SGS testing results [NFPA 701-2015]. Please note that test results may vary slightly depending on fabric colour. Note: All colours are representative only,