Verosol

434 Verocell Alta

Semi Transparent



25mm Cellular Blinds



Exceptional performance and essential colours

Features

- Alta is the perfect choice when maximum functionality is required
- This elegant 25mm cellular fabric has excellent insulation properties to help provide optimal room temperature and noise reduction. Featuring a stylish palette of 10 colours, Alta is also available in blockout fabric
- The optical white backing not only ensures maximum heat and light reflection, but also provides a uniform look from the outside regardless of the colour
- Suitable for 25mm Cellular Blinds

Care Instructions

For regular maintenance of your cellular blinds, use a soft feather duster or vacuum-clean with a soft brush dusting attachment in a low setting. Always exercise caution when spot cleaning. Use a clean lint-free cloth or sponge and dip it in warm water. Dry gently with a clean towel. Caution: Do not clean windows with any chemical products which make direct or indirect contact with the blind

For more information visit verosol.com.au or call 1800 721 404



434 Verocell Alta



Semi Transparent

Fabric Density	Semi Transparent
Composition	100% PES
Weight	164gsm ± 10%
Thickness	0.24mm ± 10%
Cell Size	25mm
Fabric Width	3000mm
Colour Fastness	7 [ISO 105-B02]
Flame Retardancy	Non Fire Retardant
Certification	Oeko-Tex 100 Class IV
Suitable Products	25mm Cellular Blinds

Fabric Colours	0100	0110	0180	0170
Solar transmittance				
Solar reflectance				
Solar absorptance				
Visible Light Transmission				
Light Absorption				
Light Reflection				
UV transmittance				
Openness factor (nominal)				
Gtot value				
FC-value				
	2			

Colour Range | 25mm Cellular Fabric

0100 White	7721 Off White	0110 Pearl	0150 Dawn	0180 Mouse	7724 Dust	0170 Espresso	7725 Bark

© Copyright 2023 Verosol Australia (ABN 36 006 221 003) Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. Thermal and optical values are tested in accordance to the European standard DIN EN 14501 and calculated and measured using DIN EN 410 for determination of luminous and solar glazing characteristics, FC-Value tested in accordance to EN5022 Reference Glazing-C. FC Classification Value Ranges: 1-FC>0.19, 2-FC>0.39, 3-FC>0.59, 4-FC>0.79, 5-FC>0.89. Specifications and other data are based on information of this document and are subject to production tolerances and/or change without prior notice. Please note that test results may vary slightly depending on fabric colour. Note: All colours are representative only.