Verosol

440 Verocell Harbour

Semi Transparent



25mm Cellular Blinds



Privacy with a natural look and feel

Features

- With an irregular linear pattern, Harbour is available in a range of six soft natural colours and a white backing that provides a uniform appearance from the outside regardles of colour
- The cellular design creates an ideal indoor environment regulating temperature and improving acoustic quality, while saving energy costs at the same time
- Harbour is also available in blockout providing excellent insulation properties and optimises room temperature
- Suitable for 25mm Cellular Blinds

Care Instructions

For regular maintenance of your cellular blinds, use a soft feather duster or vacuum-clean with a soft brush dusting attachment in a low setting. Always exercise caution when spot cleaning. Use a clean lint-free cloth or sponge and dip it in warm water. Dry gently with a clean towel. Caution: Do not clean windows with any chemical products which make direct or indirect contact with the blind

For more information visit verosol.com.au or call 1800 721 404



440 Verocell Harbour




Semi Transparent

Fabric Density	Semi Transparent
Composition	100% PES
Weight	163gsm ±10%
Thickness	0.23mm ±10%
Cell Size	25mm
Fabric Width	3000mm
Colour Fastness	7 [ISO 105-B02]
Flame Retardancy	Non Fire Retardant
Certification	Oeko-Tex 100 Class IV
Suitable Products	25mm Cellular Blinds
••••••	•••••••••••••••••••••••••••••••••••••••

Fabric Colours	0400	5247	0300	5249
Solar transmittance	20%	17%	19%	14%
Solar reflectance		69%	68%	67%
Solar absorptance				
	19%			
Light Absorption				
Light Reflection				
UV transmittance				
Openness factor (nominal)				
Gtot value				
FC-value				
		2		3

Colour Range | 25mm Cellular Fabric



© Copyright 2023 Verosol Australia (ABN 36 006 221 003) Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. Thermal and optical values are tested in accordance to the European standard DIN EN 14501 and calculated and measured using DIN EN 410 for determination of luminous and solar glazing characteristics, FC-Value tested in accordance to ENS022 Reference Glazing-C. FC Classification Value Ranges: 1-FC>0.19, 2-FC>0.39, 3-FC>0.59, 4-FC>0.79, FC>0.89, Secifications and other data are based on information available at the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Please note that test results may vary slightly depending on fabric colour. Note: All colours are representative only.