Verosol

463 Verocell Hickory

Semi Transparent



25mm Cellular Blinds



Luxurious fabric with a pure and timeless look

Features

- Hickory is a unique semi-transparent cellular fabric, with a sophisticated linen look.
- Available in a palette of six natural colour tones, it encompasses a white non-woven backing that diffuses light beautifully
- The cellular structure provides good insulation whilst creating an inspiring atmosphere in the home or office
- Hickory semi-transparent fabric has a white backing that provides a uniform appearance from the outside regardles of colour
- Suitable for 25mm Cellular Blinds

Care Instructions

For regular maintenance of your cellular blinds, use a soft feather duster or vacuum-clean with a soft brush dusting attachment in a low setting. Always exercise caution when spot cleaning. Use a clean lint-free cloth or sponge and dip it in warm water. Dry gently with a clean towel. Caution: Do not clean windows with any chemical products which make direct or indirect contact with the blind.

For more information visit verosol.com.au or call 1800 721 404



463 Verocell Hickory



Semi Transparent

Fabric Density	Semi Transparent
Composition	100% PES
Weight	235gsm ±10%
Thickness	0.37mm ±10%
Cell Size	25mm
Fabric Width	3000mm
Colour Fastness	4-5 [ISO 105-B02]
Flame Retardancy	Non Fire Retardant
Certification	Oeko-Tex 100 Class IV
Suitable Products	25mm Cellular Blinds

Fabric Colours	5631	5632	5634	5636
Solar transmittance				
Solar reflectance				
Solar absorptance				
	33%			
Light Absorption				
Light Reflection				
UV transmittance				
Openness factor (nominal)				
Gtot value				
FC-value				
	3		3	3

Colour Range | 25mm Cellular Fabric



© Copyright 2023 Verosol Australia (ABN 36 006 221 003) Information supplied was current at time of printing. Please refer to Warranty Terms & Conditions at www.verosol.com.au for more information. Thermal and optical values are tested in accordance to the European standard DIN EN 14501 and calculated and measured using DIN EN 410 for determination of luminous and solar glazing characteristics, FC-Value tested in accordance to ENS022 Reference Glazing-C. FC Classification Value Ranges: 1-FC>0.19, 2-FC>0.39, 3-FC>0.59, 4-FC>0.79, FC>0.89, Secifications and other data are based on information available at the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Please note that test results may vary slightly depending on fabric colour. Note: All colours are representative only.