

878 SilverScreen Originals

Non Transparent Metallised



Superior heat and light control available in 4 transparencies

Features

- Part of the Verosol Core Collection - metallised fabrics developed in Europe, to the highest quality standard
- Offering high performance, independent of colour
- Superior heat and glare control, excellent energy efficient solution
- Woven from 100% Polyester Trevira CS and is inherently flame retardant
- Greenguard Gold, Global GreenTagCert™ GreenRate | Level A, & LCARate GOLD, and Oeko-Tex certified
- The Originals Collection features 10 Core colours, available in 4 different transparencies
- Suitable for Pleated Blinds and Roller Blinds

Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information visit verosol.com.au or call **1800 721 404**



878 SilverScreen Originals

Non Transparent Metallised

Fabric Density	Non Transparent			Anti-Static		Yes
Composition	100% Polyester Trevira CS	PVC free	Phthalate free	Formaldehyde free	Halogen free	Antimicrobial free
Weight	142gsm ± 5%					
Thickness	0.23mm ± 5%					
Width	2400mm ± 50mm					
Colour Fastness	>5 [ISO 105-B02]					
Flame Retardancy [AS/NZS 1530.3-1999]	Ignitability Index 0 Range [0-20]	0 Range [0-10]	0 Range [0-10]	0 Range [0-10]	2 Range [0-10]	
[AS/NZS 3837-1998]	Classification Group 1					
[International]	DIN 4102 B1 (D) BS5867-2 (UK) NFPA 701 (USA)					
Aluminium Adhesion	ISO 2409 Classification 0			IR Emissivity Metal Side	0.27	
Corrosion Resistance	Metal layer EN ISO 3231					
Certification	Greenguard Gold	GreenRate Level A	LCA Rate GOLD	Oeko-Tex 100 Class IV		
	ISO 9001:2015	ISO 14001:2015	REACH	RoHS2	HPD 2.1	
Suitable Products	Roller Blinds	Pleated Blinds				

Fabric colour code	0000	0741	0711	0765	0778	0790	0920	0936	0998	0829
Solar transmittance	3%	3%	3%	2%	2%	2%	2%	2%	2%	2%
Solar reflectance outside	68%	68%	68%	68%	68%	68%	68%	68%	68%	68%
Solar absorptance	29%	29%	29%	30%	30%	30%	30%	30%	30%	30%
Luminous transmittance [VLT]	3%	2%	3%	1%	1%	0.6%	0.3%	1%	0.5%	0.2%
UV transmittance	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%
Openness factor (nominal)	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Ra (colour rendering index)	99	92	92	78	75	70	98	93	70	70

Glazing Type - Single 4mm Clear Glass

Visible light transmittance	3%
G-value / Solar heat gain coefficient	24%
Shading coefficient	28%
U-value (W/m ² K)	2.0

Glazing Type - High Performance Glazing

Visible light transmittance	2%
G-value / Solar heat gain coefficient	17%
Shading coefficient	20%
U-value (W/m ² K)	0.8

Colour Range




0000 Soft Grey

0741 Parchment

0711 Almond

0765 Gravel

0778 Cafe



0790 Espresso

0920 Pewter

0936 Dark Grey

0998 Anthracite

0829 Onyx