

815 Ultra

Transparent



Flame Retardant



Roller Blinds

Sheer fabric with excellent heat and glare control

Features

- Part of the Verosol Core Collection - fabrics developed in Europe, to the highest quality standard
- Available in matching metallised fabric range making it the perfect partner for twin blind systems
- Flame retardant fabric, providing subtle shading with good insulation for comfort all year round
- Greenguard Gold, Global GreenTag GreenRate | Level A, GreenTag LCARate Gold, and Oeko-Tex certified
- Complements heavier blackout fabrics, making it ideal for use in Verosol Twin Systems
- Ultra is suitable for Roller Blinds

Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

For more information visit verosol.com.au or call **1800 721 404**



815 Ultra

Transparent

| | | | | | | |
|--|--|-----------------------|----------------|-------------------|--------------|--------------------|
| Fabric Density | Transparent | | | | | |
| Composition | 100% Polyester Trevira CS | PVC free | Phthalate Free | Formaldehyde free | Halogen free | Antimicrobial free |
| Weight | 74gsm ± 5% | | | | | |
| Thickness | 0.23mm ± 5% | | | | | |
| Width | 2400mm ± 50mm | | | | | |
| Flame Retardancy [AS/NZS 1530.3-1999] | Ignitability Index | 0 Range [0-20] | | | | |
| | Spread of flame Index | 0 Range [0-10] | | | | |
| | Heat evolved Index | 0 Range [0-10] | | | | |
| | Smoke developed Index | 1 Range [0-10] | | | | |
| [AS/NZS 3837-1998] | Classification Group 1 | | | | | |
| [International] | DIN 4102 B1 (D) BS5867-2 (UK) NFPA 701 (USA) | | | | | |
| Certification | Greenguard Gold | Oeko-Tex 100 Class IV | ISO 9001:2015 | ISO 14001:2015 | | |
| | GreenRate Level A | GreenTag LCARate Gold | REACH | RoHS2 | | |
| Suitable Products | Pleated Blinds | | Roller Blinds | | | |

| Fabric colour code | 0000 | 0829 |
|------------------------------|------|------|
| Solar transmittance | 61% | 43% |
| Solar reflectance outside | 35% | 18% |
| Solar absorptance | 4% | 39% |
| Luminous transmittance [VLT] | 60% | 21% |
| UV transmittance | 37% | 22% |
| Openness factor (nominal) | 21% | 20% |
| Ra (colour rendering index) | 99 | 98 |

Glazing Type - Single 4mm Clear Glass

| | | |
|---------------------------------------|-----|-----|
| Visible light transmittance | 57% | 19% |
| G-value / Solar heat gain coefficient | 57% | 59% |
| Shading coefficient | 66% | 68% |
| U-value (W/m²K) | 2.9 | 2.6 |

Glazing Type - High Performance Glazing

| | | |
|---------------------------------------|-----|-----|
| Visible light transmittance | 40% | 13% |
| G-value / Solar heat gain coefficient | 26% | 28% |
| Shading coefficient | 30% | 32% |
| U-value (W/m²K) | 0.9 | 0.9 |

Colour Range

